

PROTECO-TEX 65 - prototype data sheet

2 LAYERS 20 g/m² IN POLYPROPYLENE NON WOVEN + 1 LAYER BREATHABLE FILM, ULTRASONIC BONDING

CHARACTERISTICS

PROTECO-TEX 65 is a special textile composed by 3 layers bonded by ultrasonic technology; the material is 100% recyclable.

| CHECKED CHARACTERISTICS* | NORM | UNIT OF MEASURE | VALUE |
|--------------------------|--------------|-----------------------|------------|
| Mass per unit area | EN 1849-2 | g/m ² | 65 ± 5% |
| Thickness | EN 1849-2 | mm | 0,32 ± 15% |
| Air porosity | EN 9237 | L/m ² /sec | 0,5 |
| Vapour permeability | EN ISO 12572 | g/m ² x24h | 850 |

* data deriving from a single production, subject to revision

The data provided are average, indicative data relative to current production and may be changed and updated by ELEMENTS s.r.l. and any time without any notice and at its own discretion. The recommendations and technical information provided derive from our fullest knowledge regarding the properties and uses of the product. However considering the many possible uses and possible interference of other elements not within our control, we do not take any responsibility for any possible effect. The purchaser is specifically required to determine beforehand whether the product is suitable for the intended use and thus takes full responsibility for any damage and injury that could be caused thereby.